



HPD

CERTIFICATION

45 West 23rd Street, New York, NY 10010 | Showroom - 212.256.1540
tilebar.com | info@tilebar.com | Client Services - 888.541.3840

tilebar



CORETTA COLLECTION

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

GRES PORCELAIN STONWARE - BRAND CERAMICHE COEM, BRAND CERAMICA FIORANESE BY COEM SPA

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES EVALUATION
COMPLETED: No

RESIDUALS AND IMPURITIES NOTES: The ceramic mixture used in the manufacturing of porcelain tiles may contain residual compounds derived from natural raw materials (e.g., clays, feldspars, sands) and trace impurities related to production processes. All residuals are firmly bound within the vitrified matrix formed during firing at high temperatures (above 1200°C), and therefore do not pose a risk of exposure or emission during normal use. No residuals or impurities of concern remain in the finished product.

OTHER PRODUCT NOTES: Porcelain stoneware tiles are inherently non-emitting sources of VOCs, in accordance with LEED v4 criteria. The product contains a verified share of recycled content in compliance with ISO 17889-1 and is produced using processes with low environmental impact. Manufactured in Italy using responsibly sourced raw materials, the tiles are designed for long-term durability and contribute to the indoor environmental quality of buildings. Installation recommendations include wet cutting or score-and-snap methods to limit dust dispersion.

SILICA, AMORPHOUS (PRIMARY CASRN IS 7631-86-9)

ID: 107497-59-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2025-07-22 3:17:05

%: 65.0000 - 75.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Ceramic body
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]		
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]		
MAM	GHS - Japan	H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes Precautionary List		
				Antimicrobials



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

GRES PORCELAIN STONEWARE - BRAND CERAMICHE COEM, BRAND CERAMICA FIORANESE BY COEM SPA

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES EVALUATION
COMPLETED: No

RESIDUALS AND IMPURITIES NOTES: The ceramic mixture used in the manufacturing of porcelain tiles may contain residual compounds derived from natural raw materials (e.g., clays, feldspars, sands) and trace impurities related to production processes. All residuals are firmly bound within the vitrified matrix formed during firing at high temperatures (above 1200°C), and therefore do not pose a risk of exposure or emission during normal use. No residuals or impurities of concern remain in the finished product.

OTHER PRODUCT NOTES: Porcelain stoneware tiles are inherently non-emitting sources of VOCs, in accordance with LEED v4 criteria. The product contains a verified share of recycled content in compliance with ISO 17889-1 and is produced using processes with low environmental impact. Manufactured in Italy using responsibly sourced raw materials, the tiles are designed for long-term durability and contribute to the indoor environmental quality of buildings. Installation recommendations include wet cutting or score-and-snap methods to limit dust dispersion.

SILICA, AMORPHOUS (PRIMARY CASRN IS 7631-86-9)

ID: 107497-59-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2025-07-22 3:17:05

%: 65.0000 - 75.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Ceramic body
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]		
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]		
MAM	GHS - Japan	H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes Precautionary List		
		Antimicrobials		



SUBSTANCE NOTES: Depending on the product type, certain hazardous components subject to occupational exposure limits may only be present in airborne dust generated during dry cutting, grinding, or removal operations—such as installation, demolition, or maintenance. To minimize exposure, it is recommended to use equipment with integrated dust extraction systems and/or localized exhaust ventilation. Wet cutting or score-and-snap methods are strongly advised to reduce dust dispersion.

Improper techniques, such as dry cutting with power tools, can release respirable silica dust, potentially causing acute respiratory damage. In the absence of effective ventilation systems, the use of appropriate masks or respirators, compliant with current regulations, is mandatory.

QUARTZ

ID: 14808-60-7

HAZARD DATA SOURCE: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2025-07-22 3:27:33**

?: 20.0000 - 25.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Ceramic body
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen		
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route		
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)		
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man		
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources		
CAN	IARC	Group 1 - Agent is Carcinogenic to humans		
CAN	US NIH - Report on Carcinogens	Known to be a human Carcinogen		
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]		
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]		
CAN	GHS - New Zealand	Carcinogenicity category 1		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]		
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]		
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		



SUBSTANCE NOTES: Depending on the product type, certain hazardous components subject to occupational exposure limits may only be present in airborne dust generated during dry cutting, grinding, or removal operations—such as installation, demolition, or maintenance. To minimize exposure, it is recommended to use equipment with integrated dust extraction systems and/or localized exhaust ventilation. Wet cutting or score-and-snap methods are strongly advised to reduce dust dispersion.

Improper techniques, such as dry cutting with power tools, can release respirable silica dust, potentially causing acute respiratory damage. In the absence of effective ventilation systems, the use of appropriate masks or respirators, compliant with current regulations, is mandatory.

MULLITE (AL6O5(SiO4)2)

ID: 1302-93-8

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-07-22 3:33:47	
?: 5.0000 - 6.5000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Ceramic body
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
None found			No warnings found on HPD Priority Hazard Lists	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
None found			No listings found on Additional Hazard Lists	

SUBSTANCE NOTES:



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	Inherently non-emitting source per LEED	
CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: Applicable to Coem S.p.A., including the Ceramiche Coem and Ceramica Fioranese brands. CERTIFICATE URL:	ISSUE DATE: 2025-07-22 00:00:00 EXPIRY DATE:	CERTIFIER OR LAB: None
CERTIFICATION AND COMPLIANCE NOTES: According to LEED Building Design & Construction v4, products such as ceramic tiles that are inherently non-emitting sources of VOCs are deemed fully compliant and do not require VOC emissions testing.		
TYPE 1	ISO 17889-1 Sustainability for ceramic tiles and installation materials - Part 1: Specification for ceramic tiles	
CERTIFYING PARTY: Third Party APPLICABLE FACILITIES: Applicable to Coem S.p.A., including the Ceramiche Coem and Ceramica Fioranese brands. CERTIFICATE URL: https://www.coem.it/wp-content/uploads/2023/10/30764_181023.pdf CERTIFICATION AND COMPLIANCE NOTES: N 68824	ISSUE DATE: 2024-12-17 00:00:00 EXPIRY DATE: 2025-12-17 00:00:00	CERTIFIER OR LAB: CERTIQUALITY
RECYCLED CONTENT	Extended Producer Responsibility (EPR) program - LEED compliant	
CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: Applicable to Coem S.p.A., including the Ceramiche Coem and Ceramica Fioranese brands. CERTIFICATE URL:	ISSUE DATE: 2024-12-10 00:00:00 EXPIRY DATE:	CERTIFIER OR LAB: NONE
CERTIFICATION AND COMPLIANCE NOTES: The content is also accounted for within the recycled material share, in accordance with ISO 17889-1, and has been verified by an independent third party.		
MANAGEMENT	ISO 9001:2015 Quality management systems	
CERTIFYING PARTY: Third Party APPLICABLE FACILITIES: Applicable to Coem S.p.A., including the Ceramiche Coem and Ceramica Fioranese brands. CERTIFICATE URL: https://www.coem.it/wp-content/uploads/2023/12/17291_231220_UN.pdf CERTIFICATION AND COMPLIANCE NOTES:	ISSUE DATE: 2023-12-20 00:00:00 EXPIRY DATE: 2026-12-12 00:00:00	CERTIFIER OR LAB: CERTIQUALITY
MANAGEMENT	ISO 14001:2004 Environmental management systems	
CERTIFYING PARTY: Third Party APPLICABLE FACILITIES: Applicable to Coem S.p.A., including the Ceramiche Coem and Ceramica Fioranese brands. CERTIFICATE URL: https://www.coem.it/wp-content/uploads/2023/04/UNI-EN-ISO-14001-2015.pdf CERTIFICATION AND COMPLIANCE NOTES:	ISSUE DATE: 2022-11-17 00:00:00 EXPIRY DATE: 2025-09-19 00:00:00	CERTIFIER OR LAB: CERTIQUALITY
3	ISO 45001:2023	
CERTIFYING PARTY: Third Party APPLICABLE FACILITIES: Applicable to Coem S.p.A., including the Ceramiche Coem and Ceramica Fioranese brands. CERTIFICATE URL: https://www.coem.it/wp-content/uploads/2024/08/29579_240725_UN.pdf CERTIFICATION AND COMPLIANCE NOTES: Occupational health and safety management systems	ISSUE DATE: 2024-07-25 00:00:00 EXPIRY DATE: 2027-07-28 00:00:00	CERTIFIER OR LAB: CERTIQUALITY

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.



TILING METHODS - MAINTENANCE

MANUFACTURER (OR GENERIC): **Coem Spa**

HPD URL: https://www.coem.it/wp-content/uploads/2024/06/Download-Coem_tech-area-24.25.jpg

ACCESSORY TYPE: **Other**

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES: **RECOMMENDED USE OF PORCELAIN TILES**

Section 5: General Notes

Coem S.p.A. is an Italian company with a long-standing industrial tradition, founded in the early 1970s in Fiorano Modenese, at the heart of the Emilia-Romagna ceramic district. Through its two brands, Ceramiche Coem and Ceramica Fioranese, the company has established itself internationally for the production of high-quality porcelain stoneware tiles, inspired by the beauty of natural stone and reinterpreted with cutting-edge technologies and contemporary design.

From the very beginning, Coem has combined aesthetics, technical research, and sustainability, promoting a production philosophy rooted in environmental respect and people's well-being. Its commitment to sustainability is reflected in low-impact manufacturing processes, the use of renewable energy sources such as photovoltaic systems, and the selection of traceable raw materials, often enriched with a share of recycled content verified by third parties, in accordance with ISO 17889-1.

The company holds certifications including ISO 14001 for environmental management, ISO 45001 for occupational health and safety, EMAS for eco-compatible management, and ISO 17889-1, which assesses the sustainability of ceramic products from environmental, social, and economic perspectives. Thanks to the synergy between technological innovation, design excellence, and environmental responsibility, Coem creates ceramic surfaces that enhance every space—from private residences to urban architecture—contributing to the quality of living environments through durable, safe, and visually distinctive materials.



Section 6: References

MANUFACTURER INFORMATION

MANUFACTURER: **Coem SpA**
ADDRESS: **VIA CAMEAZZO, N° 25**
VIA STRADONE SECCHIA, 32 ROTEGLIA DI CASTELLARANO (RE)
FIORANO MODENESE, MODENA 41042
COUNTRY: **ITALY**

WEBSITE: <https://www.coem.it/>
CONTACT NAME: **COEM SPA - ELISA TONELLI**
TITLE: **QHSE MANAGER**
PHONE: **+39 0536 993 511**
EMAIL: elisa.tonelli@coem.it

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.