# FLEETWOOD RIGID CORE CLICK





#### POWERED BY PERFORMANCE AND GOOD LOOKS

Produced in collaboration with top product designer Stacy Garcia, Fleetwood LVT is a high-quality, wood-look Luxury Vinyl Tile engineered for high-traffic residential and commercial spaces. The designer-led collection features high-definition wood prints on planks as well as builtin chevron and parquet patterns, all with realistic micro-beveled edges. It can be very labor-intensive to lay patterns like these, but with Fleetwood, there's no cutting and less scrap, so installation is a breeze.

Like all TileBar LVT, Fleetwood features layer-by-layer construction that offers practical benefits: It's waterproof, sound-absorbing, and resistant to scratches, stains, and indentations. With the Rigid Core Click installation system, planks click and lock into each other, allowing for a DIY project that doesn't require a drop of glue—even over existing floors. This quickand-easy system, along with Fleetwood's durability, make it a flooring solution that simplifies life as much as it beautifies it.

















### WHY FLEETWOOD LVT?

- · Engineered for high-traffic residential and commercial use
- ProTX<sup>™</sup> topcoat and 20-mil wear layer for durability
- · High-definition print for a realistic wood look
- · Micro-beveled edges
- · Resists stains, scratches, and indentations
- · Waterproof core protects the subfloor.
- Sound-absorbing
- · Comfortable underfoot
- Budget-friendly
- · Easy to clean and maintain

## **CHEVRON**









DOLPHIN CHEVRON







PLUME CHEVRON

STARLING CHEVRON

SILVER CHEVRON

#### **PARQUET**







BEAR PARQUET

DOLPHIN PARQUET

MOCHA PARQUET







PLUME PARQUET

STARLING PARQUET

SILVER PARQUET

#### **PLANK**







BEAR





PLUME

STARLING

SILVER

# FLEETWOOD RIGID CORE CLICK



RIGID CORE CLICK SPECIFICATIONS				
All Colors in Stock				
Available Sizes:	12" x 48" Chevron   12" x 24" Parquet   6" x 48" Plank			
Construction:	Rigid Core Click Luxury Vinyl Tile			
Classification:	ASTM F3261 Class I Type B Grade I Backing Class B			
Total Thickness:	5.0 mm (0.200") (Includes 1.0 mm Acoustic Backing)			
Wear Layer Thickness:	20 mil (0.50 mm)			
Edge Treatment:	Micro-Bevel			
Finish:	ProTX™			
Colorways:	18			
Installation Method:	Click			
Locking System:	UNILIN			
Backing Color:	Black			
	12"x48" Chevron	12"x24" Parquet	6"x48" Plank	
Pieces per Carton:	6	14	14	
Weight per Carton:	43.21 lbs	45.86 lbs	45.2 lbs	
Square Feet per Carton:	44.03	28.04	27.39	
Cartons per Pallet:	45	54	54	

#### APPLICATIONS

Commercial Spaces: Foot traffic only and rolling loads under 500 lbs. Educational Institutions, Healthcare, Senior Living, Hospitality, Retail, Workplace

Residential: Multi-Family, Single Family



20 MIL RIGID CORE CLICK			
Dimensional Stability (ASTM F2199):	Passes - Max 0.020 in/lin ft		
Squareness (ASTM F540):	Passes - Max ± 0.010		
Flatness (ISO 24337)	Passes		
Opening (ISO 24337)	Passes		
Ledging (ISO 24337)	Passes		
Residual Indentation (ASTM F1914):	Avg. ≤ 0.007 in. (0.16 mm)   No puncture thru wear layer/ print film		
Static Load (ASTM F970 mod.):	Passes – Modified Test (anything beyond 250 PSI) = 1,500 PSI; Residual Indent ≤ 0.005"		
Acoustics (ASTM E492)	54 - Over 6" Concrete Slab   68 - Over 6" Concrete Slab and Drop Ceiling		
Flooring Radiant Panel (ASTM E648):	Passes - Class 1; ≥ 0.45 watts/cm2		
Smoke Density (ASTM E662):	Passes - ≤ 450		
Slip Resistance (ASTM D2047):	Passes - SCOF≥ 0.6		
Resistance to Light (ASTM F1515):	Passes - ΔΣ≤ 8.0		
Chemical Resistance (ASTM F925):	Excellent		
Resistance to Heat (ASTM F1514):	Passes		
Castor Chair (EN 425)	Passes		

TYPE	COLOR	20 MIL RIGID CORE CLICK	
12"x48" Chevron	Bear	•	
	Starling	•	
	Plume	•	
	Mocha	•	
	Silver	•	
	Dolphin	•	
12"x24" Parquet	Bear	•	
	Starling	•	
	Plume	•	
	Mocha	•	
	Silver	•	
	Dolphin	•	
6"X48" PLANK	Bear	•	
	Starling	•	
	Plume	•	
	Mocha	•	
	Silver	•	
	Dolphin	•	
● In Stock   ■ Available to Order			