

HEIGHTS XL LVT

WOOD-LOOK LUXURY VINYL
28 MIL RIGID CORE CLICK



TECHNICAL DATA

| | |
|----------------------|---|
| Available Sizes | 9"x60" |
| Classification | ASTM F3261 Class I Type B, Grade 1, Backing Class B |
| Total Thickness: | 6.0mm (0.240") (Includes 1.0mm Acoustic Backing) |
| Wear Layer Thickness | 28 mil (0.70 mm) |
| Edge Treatment | Micro-Bevel |
| Finish | ProTx™ |
| Colors | 6 |
| Installation Method | Click |
| Backing Color | Black |

PACKAGING & APPLICATIONS

| | |
|--------------------------|--|
| Installation Method | Click |
| Pieces/Carton | 8 pcs |
| Weight/Carton | 63.4 lbs |
| ft ² / Carton | 30.0525 |
| Carton/Pallet | 44 |
| Residential Applications | Multi-Family, Single Family |
| Commercial Applications | Foot Traffic Only and Rolling Loads under 500 lbs. Educational Institutions, Healthcare, Senior Living, Hospitality, Retail, Workplace |

TESTING SPECIFICATIONS

| | | |
|---------------------------------------|--------------------|--|
| Dimensional Stability | ASTM F2199 | Passes - Max 0.020 in./lin ft |
| Squareness | ASTM F540 | Passes - Max ± 0.010 |
| Flatness | ISO 24337 | Passes |
| Opening | ISO 24337 | Passes |
| Ledging | ISO 24337 | Passes |
| Residual Indentation | ASTM F1914 | Avg. ≤ 0.007 in (0.16mm) No puncture through wear layer / print film |
| Static Load | ASTM F970 Modified | Passes - Modified Test (anything beyond 250 PSI) - 1,500 PSI: Residual Indent ≤ 0.005" |
| Impact Isolation Class | ASTM E492 | 54 - Over 6" Concrete Slab 64 - Over Concrete Slab and Drop Ceiling |
| Sound Transmission Class | ASTM E90 | Delta IIC (ΔIIC) - 16 |
| Sound Transmission Reduction Radiated | ASTM E2179 | Passes - ≤ 450 |
| Flooring Radiant Panel | ASTM E648 | Passes - Class 1: ≥ 0.45 watts/cm ² |
| Smoke Density | ASTM E662 | Passes - ≤ 450 |
| Slip Resistance | ASTM D2047 | Passes - SCOF ≥ 0.6 |
| Resistance to Light | ASTM F1515 | Passes - ΔΣ ≤ 8.0 |
| Chemical Resistance | ASTM F925 | Passes - ΔΣ ≤ 8.0 |
| Resistance to Heat | ASTM F1514 | Passes |
| Castor Chair | EN 425 | Passes |



HEIGHTS XL LVT

WOOD-LOOK LUXURY VINYL

28 MIL LOOSE LAY



TECHNICAL DATA

| | |
|----------------------|--|
| Available Sizes | 9"x60", 6" x 24" |
| Classification | ASTM F1700 Class III, Type B |
| Total Thickness: | 4.5mm (0.180") (Includes 1.0mm Acoustic Backing) |
| Wear Layer Thickness | 28 mil (0.70 mm) |
| Edge Treatment | Micro-Bevel |
| Finish | ProTx™ |
| Colors | 6 |
| Installation Method | Click |
| Backing Color | Black |

PACKAGING & APPLICATIONS

| | | |
|--------------------------|--|---------------------|
| Installation Method | Loose Lay or Perimeter / Grid / Full Spread Adhesive | |
| Pieces/Carton | 9" x 60": 10 pcs | 6" x 24": 16 pcs |
| Weight/Carton | 9" x 60": 54.13 lbs | 6" x 24": 22.46 lbs |
| ft ² / Carton | 9" x 60": 37.5 sqft | 6" x 24": 16 sqft |
| Cartons / Pallet | 9" x 60": 48 | 6" x 24": 96 |
| Residential Applications | Multi-Family, Single Family | |

Applications
No Adhesive: Foot traffic only. No rolling loads > For small spaces only
Perimeter Adhesive Installation: Moderate sized rooms. Moderate traffic.
Full-Spread Adhesive: Heavy foot traffic and rolling loads.

TESTING SPECIFICATIONS

| | | |
|---------------------------------------|--------------------|--|
| Dimensional Stability | ASTM F2199 | Passes - Max 0.020 in./lin ft |
| Squareness | ASTM F540 | Passes - Max ± 0.010 |
| Flatness | ISO 24337 | Passes |
| Opening | ISO 24337 | Passes |
| Ledging | ISO 24337 | Passes |
| Residual Indentation | ASTM F1914 | Avg. ≤ 0.007 in (0.16mm) No puncture through wear layer / print film |
| Static Load | ASTM F970 Modified | Passes - Modified Test (anything beyond 250 PSI) - 1,500 PSI: Residual Indent ≤ 0.005" |
| Impact Isolation Class | ASTM E492 | 50 - Over 6" Concrete Slab 64 - Over Concrete Slab and Drop Ceiling |
| Sound Transmission Class | ASTM E90 | Delta IIC (ΔIIC) - 16 |
| Sound Transmission Reduction Radiated | ASTM E2179 | Passes - ≤ 450 |
| Flooring Radiant Panel | ASTM E648 | Passes - Class 1: ≥ 0.45 watts/cm ² |
| Smoke Density | ASTM E662 | Passes - ≤ 450 |
| Slip Resistance | ASTM D2047 | Passes - SCOF ≥ 0.6 |
| Resistance to Light | ASTM F1515 | Passes - ΔΣ ≤ 8.0 |
| Chemical Resistance | ASTM F925 | Passes - ΔΣ ≤ 8.0 |
| Resistance to Heat | ASTM F1514 | Passes |
| Castor Chair | EN 425 | Passes |

