

# RENEW LVT



## POWERED BY PERFORMANCE

ReNew is the confident solution for light commercial and residential spaces. ReNew is the perfect and affordable solution for your residential project and light commercial uses. Our LVT products have been specifically engineered to offer the best performance and maintenance while keeping our commitment to providing great design for every budget. Offering a wide range of looks from natural woods to modern stone, ReNew outlasts the competition in both style & durability.

## WHAT WE LOVE ABOUT RENEW LVT

High-definition print for a realistic wood look

Waterproof, stain-proof, and scratch-resistant

Easy to clean and maintain

High-Definition Design



PET FRIENDLY



WATERPROOF



CASTER APPROVED



PHTHALATE FREE



ISO 9001



ISO 14001



floor score

## WOOD LOOKS

Glue Down



White Oak Vintage

Aspen Pecan Chelsea Grey

Scarlet Oak Studio

Bur Oak Veranda

Lofty Oak Anthracite

Spice Birch Moon



Scarlet Oak Fawn

Metro Oak Brown Sugar

Majestic Maple Natural

Opulence Oak Gingered

Charming Chestnut Amber Glow

Oregon Maple Tulatin

## CONCRETE LOOKS

Glue Down



Metalcrete Crest

Metalcrete Mountain Dusk

Metalcrete Wildmist

Metalcrete Platinum

Metalcrete Pewter

Metalcrete Charcoal


## AVAILABLE FOR SPECIAL ORDER

Glue Down

Minimum order 1 palette with an 8-12 week lead time

## SIZE & FORMATS

2 Sizes



6\"x48\"



12\"x24\"



## AVAILABILITY

In Stock

### GLUE DOWN | 6\"X 48\" | 12 MIL

<input checked="" type="radio"/> White Oak Vintage	<input checked="" type="radio"/> Aspen Pecan Chelsea Grey	<input checked="" type="radio"/> Scarlet Oak Studio	<input checked="" type="radio"/> Bur Oak Veranda	<input checked="" type="radio"/> Lofty Oak Anthracite	<input checked="" type="radio"/> Spice Birch Moon
<input checked="" type="radio"/> Scarlet Oak Fawn	<input checked="" type="radio"/> Metro Oak Brown Sugar	<input checked="" type="radio"/> Majestic Maple Natural	<input checked="" type="radio"/> Opulence Oak Gingered	<input checked="" type="radio"/> Charming Chestnut Amber Glow	<input checked="" type="radio"/> Oregon Maple Tulatin

### GLUE DOWN | 12\"X 24\" | 12 MIL

<input type="radio"/> Metalcrete Crest	<input type="radio"/> Metalcrete Mountain Dusk	<input type="radio"/> Metalcrete Wildmist	<input type="radio"/> Metalcrete Platinum	<input type="radio"/> Metalcrete Pewter	<input type="radio"/> Metalcrete Charcoal
--	--	---	---	---	---

### GLUE DOWN | 6\"X 48\" | 6 MIL

<input type="radio"/> White Oak Vintage	<input checked="" type="radio"/> Aspen Pecan Chelsea Grey	<input checked="" type="radio"/> Scarlet Oak Studio	<input type="radio"/> Bur Oak Veranda	<input type="radio"/> Lofty Oak Anthracite	<input type="radio"/> Spice Birch Moon
<input type="radio"/> Scarlet Oak Fawn	<input checked="" type="radio"/> Metro Oak Brown Sugar	<input type="radio"/> Majestic Maple Natural	<input checked="" type="radio"/> Opulence Oak Gingered	<input type="radio"/> Charming Chestnut Amber Glow	<input type="radio"/> Oregon Maple Tulatin

### GLUE DOWN | 12\"X 24\" | 6 MIL

<input checked="" type="radio"/> Metalcrete Crest	<input type="radio"/> Metalcrete Mountain Dusk	<input type="radio"/> Metalcrete Wildmist	<input checked="" type="radio"/> Metalcrete Platinum	<input type="radio"/> Metalcrete Pewter	<input type="radio"/> Metalcrete Charcoal
---	--	---	--	---	---

# RENEW LVT

WOOD & CONCRETE LOOK LUXURY VINYL  
12 MIL GLUE DOWN



## TECHNICAL DATA

Available Sizes	6" x 48"   12" x 24"
Classification	ASTM F1700 Class III, Type B
Total Thickness:	2.0 mm (0.80")
Wear Layer Thickness	12mil (0.30mm)
Edge Treatment	Square Edge
Finish	ProTx™
Colors	18
Installation Method	Full Spread Adhesive
Backing Color	Black

## PACKAGING & APPLICATIONS

Installation Method	Full Spread Adhesive	
Pieces/Carton	20 pcs	
Weight/Carton	6" x 48": 34.3 lbs	12" x 24": 32.96 lbs
ft <sup>2</sup> / Carton	6" x 48": 42.37 sqf	12" x 24": 42.04 sqft
Carton/Pallet	60	
Residential Applications	Multi-Family, Single Family	
Commercial Applications	Foot Traffic Only and Rolling Loads under 500 lbs. Educational Institutions, Healthcare, Senior Living, Hospitality, Retail, Workplace	

## TESTING SPECIFICATIONS

Dimensional Stability	ASTM F2199	Passes - Max 0.020 in/lin ft
Flexibility	ASTM F137	Passes - 1" Mandrel - No Crack/Break
Squareness	ASTM F540	Passes - Max 0.010"
Residual Indentation	ASTM F1914	Passes - < 8% Avg / 10% Single Value
Static Load	ASTM F970 Modified	Passes - Modified Test (anything beyond 250 PSI) = 2,000 PSI; Residual Indent ≤ 0.005"
Flooring Radiant Panel	ASTM E648	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density	ASTM E662	Passes - ≤ 450
Slip Resistance	ASTM D2047	Passes - SCOF ≥ 0.6
Resistance to Light	ASTM F1515	Passes - ΔΣ ≤ 8.0
Chemical Resistance	ASTM F925	Excellent
Resistance to Heat	ASTM F1514	Passes
Castor Chair	EN 425	Passes



# RENEW LVT

WOOD & CONCRETE LOOK LUXURY VINYL

6 MIL GLUE DOWN | SEE CHART FOR AVAILABILITY



## TECHNICAL DATA

Available Sizes	6" x 48"   12" x 24"
Classification	ASTM F1700 Class III, Type B
Total Thickness:	2.0 mm (0.80")
Wear Layer Thickness	6mil (0.15mm)
Edge Treatment	Square Edge
Finish	ProTx™
Colors	18
Installation Method	Full Spread Adhesive
Backing Color	Black

## PACKAGING & APPLICATIONS

Installation Method	Full Spread Adhesive	
Pieces/Carton	20 pcs	
Weight/Carton	6" x 48": 34.3 lbs	12" x 24": 32.96 lbs
ft <sup>2</sup> / Carton	6" x 48": 42.37 sqf	12" x 24": 42.04 sqft
Carton/Pallet	60	
Residential Applications	Multi-Family, Single Family	
Commercial Applications	Foot Traffic Only and Rolling Loads under 500 lbs. Educational Institutions, Healthcare, Senior Living, Hospitality, Retail, Workplace	

## TESTING SPECIFICATIONS

Dimensional Stability	ASTM F2199	Passes - Max 0.020 in/lin ft
Flexibility	ASTM F137	Passes - 1" Mandrel - No Crack/Break
Squareness	ASTM F540	Passes - Max 0.010"
Residual Indentation	ASTM F1914	Passes - < 8% Avg / 10% Single Value
Static Load	ASTM F970 Modified	Passes - Modified Test (anything beyond 250 PSI) = 2,000 PSI; Residual Indent ≤ 0.005"
Flooring Radiant Panel	ASTM E648	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density	ASTM E662	Passes - ≤ 450
Slip Resistance	ASTM D2047	Passes - SCOF ≥ 0.6
Resistance to Light	ASTM F1515	Passes - ΔΣ ≤ 8.0
Chemical Resistance	ASTM F925	Excellent
Resistance to Heat	ASTM F1514	Passes
Castor Chair	EN 425	Passes

